

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (original) An electronic controllable pipette comprising
 - a piston actuated in a cylinder by a motor,
 - a control system enabling the piston to be moved under a given pipetting function consisting of several steps,
 - setting keys (7, 8, 9) for selecting the desired pipetting function and the related settings,
 - a switch (1) activating the function steps when depressed, and
 - a display (3),characterised in that
 - the control system comprises a change function, whose activation allows a selected function to be changed in the course of its operation, and when
 - the change function can be activated, the operation of a given setting key changes,
 - the changed operation of this setting key is shown on the display, and
 - the change operation can be activated by depressing this setting key.
2. (original) A pipette as defined in claim 1, in which the change function comprises cancelling a selected pipetting function, switching from the selected pipetting function to another, or combining an additional function with the selected pipetting function.
3. (currently amended) A pipette as defined in claim 1 ~~or~~ 2, in which the setting keys include at least one selection key (7, 8), depression of this selection key allowing a

pipetting function or setting indicated on the display to be selected for use, and depression of a selection key enabling activation of the change function.

4. (original) A system for controlling an electronic pipette, the pipette comprising

- a piston actuated in a cylinder by a motor, the piston being movable by means of the control system according to a given pipetting function consisting of several steps,
- setting keys (7, 8, 9) for selecting the desired pipetting function and the related settings,

- a switch (1) which activates the function steps when depressed, and
- a display (3)

characterised in that

- the control system has a change function, whose activation allows a change of a selected function in the course of its operation, and when
- the change function can be activated, the operation of a given setting key changes,
- the changed operation of this setting key is indicated on the display, and
- the change operation can be activated by depressing this setting key.

5. (new) A pipette as defined in claim 2, in which the setting keys include at least one selection key (7, 8), depression of this selection key allowing a pipetting function or setting indicated on the display to be selected for use, and depression of a selection key enabling activation of the change function.